

DESCRIPTION

Series 110 Channel Framed Mirrors come with a bright polished stainless steel frame for years of use, and are supplied with an internal locking system ideal for institutional and commercial installations. Mounting bracket secures directly to wall and is hidden after installation. Safety tape prevents glass shards from falling should breakage occur.

TECHNICAL DATA

Mirror: 5mm thick float plate glass, electro-copper backed to prevent silver spoilage. GEN-MAC IMPACT TAPE®, a shatter-proofing Category II mirror backing, is factory applied. Tape meets 16 FR 1201-11 and ANSI Z97.1 requirements.

Backing: Full-sized expanded polystyrene sheet.

Back Plates: 22 gauge galvanized steel with punched key slots.

Wall Bracket: 22 gauge galvanized steel with shoulder rivets.

Lock Springs: 24 gauge galvanized steel.

Channel: ½" x ½" x ½" bright polished stainless steel with mitered corners.

SPECIFICATION

Channel Framed Mirrors with shatterproof backing shall be Series 110 as manufactured by JSM, Rancho Dominguez, CA. Mirrors shall be ____" wide x ____" high.

NOTES

1. Mirror sizes indicate nominal glass size. **Actual finished mirror sizes are ¼" larger.**
2. Always order mirrors by width first, then height.

INSTALLATION

1. Attach mounting bracket to wall using mechanical fasteners appropriate for existing wall conditions.
2. Place mirror face down on flat surface and slide snap-lock springs under the neck of the key slots on the bottom channel. (see 1, 2 & 3 below)
3. Mount mirror on wall bracket making sure shoulder rivets are fully seated in the neck portion of the key slots. (see 4)

GUARANTEE

110 Series Channel Framed Mirrors are guaranteed for ten years against silver spoilage with proper maintenance.

