

### DESCRIPTION

Series 950 Angle Framed Mirrors come with a #4 satin finish stainless steel frame for years of use, and are supplied with an internal locking system ideal for institutional and commercial installations. Mounting bracket secures directly to wall and is hidden after installation. Laminated glass offers break and shatter resistance, but reflective quality may vary.

### TECHNICAL DATA

Mirror: 5mm thick laminated glass, electro-copper backed to prevent silver spoilage.  
 Backing: Full-sized expanded polystyrene sheet.  
 Back Plates: 22 gauge galvanized steel with punched key slots.  
 Wall Bracket: 22 gauge galvanized steel with shoulder rivets.  
 Lock Springs: 24 gauge galvanized steel.  
 Frame: 3/4" x 3/4" x 3/8" 18 gauge type 304 stainless steel with #4 satin finish and welded corners.

### SPECIFICATION

Angle Framed Mirrors with laminated glass shall be Series 950 as manufactured by JSM, Rancho Dominguez, CA. Mirrors shall be \_\_\_\_" wide x \_\_\_\_" high.

### NOTES

1. Mirror sizes indicate nominal glass size. **Actual finished mirror sizes are 7/8" larger.**
2. Always order mirrors by width first, then height.
3. For laminated glass mirrors, the reflective quality and color of surface may differ from that of standard glass.

### INSTALLATION

1. Attach mounting bracket to wall using mechanical fasteners appropriate for existing wall conditions.
2. Place mirror face down on flat surface and slide snap-lock springs under the neck of the key slots on the bottom channel. (see 1, 2 & 3 below)
3. Mount mirror on wall bracket making sure shoulder rivets are fully seated in the neck portion of the key slots. (see 4)

### GUARANTEE

950 Series Angle Framed Mirrors are guaranteed for ten years against silver spoilage with proper maintenance.

